

PRODUCT DATASHEET

Enhanced anti-glare,Led spot light HYD-343S-7W*2 4000K



Application

- Home
- Restaurant
- Exhibition Hall
- Stage
- Conference Room
- Clothing Store

Benefits

- · Flicker free
- It can be used for emphasis lighting and decorative lighting
- Spot light have prominent advantages in commercial lighting
- No secondary light spot, it can create a wall washing effect

Features

- Warranty 5 years
- PC,Good light transmission
- Small size, light weight, buckle design, easy to install
- Die-cast aluminum, good heat dissipation, reduce light decay





Electrical Data

Nominal wattage (W)	7W*2	
Nominal Voltage (V)	220-240 V	
Mains Frequency (Hz)	50	
Nominal Current (mA)	122	
LED Driver Current (mA)	300	
LED Driver Voltage (VDC)	15-24	
LED Driver Efficiency (%)	80%	
Power Factor λ	0.5C	
Total harmonic distortion (%)		
Operating mode	External LED driver	

Photometrical data

Luminous flux ±10% (lm)	1630 lm	
Luminous efficacy	111 lm/w	
Color temperature	4000K	
Light color (designation)	Natural White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤5 SDCM	
Luminous intensity/cd	3886	
Flickering	Flicker free	
Beam angle	32 °	






Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

4000K



Dimensions & Weight

Diameter (mm)	170*85
Height (mm)	40
Product weight (g) / Housing	328



Material & Colors

Product color	White	
Housing color	White	
Body material	Aluminum	
Cover material	PC	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-20°C~+45 °C		
Temperature range at storage	-20°C~+60 °C		
Type of connection	Screwless terminal		
Type of protection	IP20		
Dimmable	No		
Mounting type	Recessed		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	155*73		
LED module replaceable	Not replaceable		
With light source	Yes		




Certificates & Lifespan

Life (h)	50,000
Certificates	CB CE LVD EMC
Standards	ISO9001:2015

Logistical Data

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-343S-7W*2	•••	:		

Installation Method



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.